





Made in the U.S.a.

105 Harrison Street, American Falls, Idaho 83211

www.ams-samplers.com

ams@ams-samplers.com

Phone: 208-226-2017 | 800-635-7330

Fax: 208-226-7280



P() M/ERPR() BETM 952() - SK

MAST & PROBE

Standard hammer: 200 ft-lb Horizontal traverse: 26.5" Head travel rate up: 16 sec Head travel rate down: 13 sec

Probe stroke: 72" Foot vertical stroke: 36" Down force: 26,300 lb. Pull-up force: 38,000 lb. In / Out travel: 12" Mast extended height: 178"

Probe angles: 80 ° to 100 °

Standard auger: 2,400 ft-lb 2-speed (Low: 0-40rpm/ High: 0-140 rpm)

ENGINE

Horsepower: Carrier dependent Hydaulic oil pressure: 2,400 psi Hydraulic flow rate: 16 gpm

Fuel type: Carrier dependent

Hydraulic oil cooler: Vehicle dependent Hydraulic oil capacity: Vehicle dependent

DIMENSIONS

Weight: 3,200 lb.

Overall length: 69" - 73"

Overall width: 66"

Overall height (folded): 110" (124")



AMS POWERPROBE CUSTOMIZATION

Geotechnical Options

- CPT, CPTu, Seismic CPT
- Single Point Anchoring System (CPT)
- Dual Point Anchoring System (CPT)
- · Cat Head Assembly (SPT)

Options and Accessories

- 3,400 ft-lb Auger Drive Head
- 350-ft-lb Direct Push Hammer
- 3,000 lb. Hydraulic Hi-Speed Winch



CUSTOM/ER

Everyone at AMS is dedicated to exceeding our customers' needs and expectations. From answering questions about availability, use and care, to developing customized products, we're here to help. Call 208-226-2017 or 1-800-635-7330 for more information.





Equipping the World to Sample the Earth